

Safety Data Sheet

Issue Date: 23-Nov-2015

Revision Date: 04-Dec-2015

Version 1

1. IDENTIFICATION

Product Identifier

Product Name Angelus No. 530 Shine & Dye

Other means of identification

SDS # ASP-006

UN/ID No UN1263

Recommended use of the chemical and restrictions on use

Recommended Use Shoe shine/dye.

Details of the supplier of the safety data sheet

Supplier Address

Angelus Shoe Polish Co.
Florence Ave.
Santa Fe Springs, CA 90670
Ph: 562-941-4242

Emergency Telephone Number

Emergency Telephone (24 hr) INFOTRAC 1-352-323-3500 (International)
1-800-535-5053 (North America)

2. HAZARDS IDENTIFICATION

Appearance Transparent to deep color liquid

Physical state Liquid

Odor Slightly sweet, Alcohol

Classification

Specific target organ toxicity (single exposure)	Category 1
Specific target organ toxicity (repeated exposure)	Category 1
Aspiration toxicity	Category 1
Flammable Liquids	Category 3

Hazards Not Otherwise Classified (HNOC)

May be harmful if swallowed

Signal Word

Danger

Hazard statements

Causes damage to organs
Causes damage to organs through prolonged or repeated exposure
May be fatal if swallowed and enters airways
Flammable liquid and vapor



Precautionary Statements - Prevention

Do not breathe dust/fume/gas/mist/vapors/spray
 Wash face, hands and any exposed skin thoroughly after handling
 Do not eat, drink or smoke when using this product
 Keep away from heat/sparks/open flames/hot surfaces. — No smoking
 Keep container tightly closed
 Ground/bond container and receiving equipment
 Use explosion-proof equipment
 Use only non-sparking tools
 Take precautionary measures against static discharge
 Wear protective gloves/protective clothing/eye protection/face protection

Precautionary Statements - Response

IF exposed: Call a POISON CENTER or doctor/physician
 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower
 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician
 Do not induce vomiting
 IN CASE OF FIRE: Use CO₂, dry chemical, or foam for extinction

Precautionary Statements - Storage

Store locked up
 Store in a well-ventilated place. Keep cool

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Other hazards

Toxic to aquatic life with long lasting effects

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS No	Weight-%
Ethyl Alcohol	64-17-5	>40
Stoddard solvent	8052-41-3	>8
Methanol	67-56-1	<4
Isopropyl Alcohol	67-63-0	<1

If Chemical Name/CAS No is "proprietary" and/or Weight-% is listed as a range, the specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. FIRST-AID MEASURES

First Aid Measures

General Advice	Provide this SDS to medical personnel for treatment.
Eye Contact	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation occurs.
Skin Contact	IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. Wash contaminated clothing before reuse. Get medical attention if irritation occurs.
Inhalation	Remove exposed individual(s) to fresh air for 20 minutes. Consult a physician / poison center if individual's condition declines or if symptoms persist. If not breathing, give artificial respiration. If breathing is difficult, oxygen should be administered by qualified personnel.
Ingestion	IF SWALLOWED: call a poison control center or physician immediately. Do not induce vomiting. If vomiting occurs naturally, have victim lean forward to reduce risk of aspiration. If drowsy or unconscious, do not give anything by mouth; place individual on the left side with head down.

Most important symptoms and effects**Symptoms**

Contact with eyes may cause stinging, tearing, redness, or swelling. Contact with skin may result in redness and burning. If inhaled, symptoms may include, irritation of the nose, throat, and respiratory tract. Swallowing may result in gastrointestinal irritation (nausea, vomiting, and diarrhea), headache, dizziness, shortness of breath, drunken behavior, visual disturbance, fatigue, unconsciousness, complete blindness, and death. Alcohol consumed before or after exposure may worsen effects. Ingestion of moderate quantities of methanol produces acidosis.

Indication of any immediate medical attention and special treatment needed**Notes to Physician**

Treat as methyl alcohol poisoning. Treatment should include the following: Hemodialysis, the intravenous administration of ethanol (10ml per hour) to interfere with the metabolism of methyl alcohol; and the administration of sodium bicarbonate to correct acidosis. Gastric lavage may be effective by physician within 4 hours of ingestion.

5. FIRE-FIGHTING MEASURES**Suitable Extinguishing Media**

Regular foam, water fog, CO₂, dry chemical, Alcohol foam.

Unsuitable Extinguishing Media Not determined.

Specific Hazards Arising from the Chemical

Flammable liquid and vapor. Vapors may travel or be moved by air currents and ignited by pilot lights, other flames, smoking, sparks, static discharges or other ignition sources at locations distant from product handling point. Vapors may settle in low or confined areas or travel a long distance to an ignition source and flash back explosively. This material may produce a floating fire hazard. Flame may be invisible. Approach fire with caution.

Hazardous Combustion Products Carbon monoxide. Carbon dioxide (CO₂). Various hydrocarbons.

Explosion Data

Sensitivity to Static Discharge Prevent electrostatic charge build-up by using common bonding and ground techniques.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Never use welding or cutting torch on or near containers that are full or empty because product (even slight residue) can ignite explosively. Cool fire exposed containers with water spray to prevent vapor pressure build up.

6. ACCIDENTAL RELEASE MEASURES**Personal precautions, protective equipment and emergency procedures****Personal Precautions**

Wear protective clothing as described in Section 8 of this safety data sheet.

Environmental precautions**Environmental precautions**

Prevent from entering into soil, ditches, sewers, waterways and/or groundwater. See Section 12, Ecological Information. See Section 12 for additional Ecological Information.

Methods and material for containment and cleaning up**Methods for Containment**

Persons not wearing protective equipment should leave area until cleanup is completed. Remove all sources of ignition. Prevent further leakage or spillage if safe to do so. Soak up and contain spill with an inert (i.e. vermiculite, dry sand or earth) absorbent material.

Methods for Clean-Up

Use non-sparking hand tools and explosion-proof electrical equipment. Sweep up and shovel into suitable containers for disposal. For waste disposal, see section 13 of the SDS.

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on Safe Handling

Do not breathe dust/fume/gas/mist/vapors/spray. Wash face, hands, and any exposed skin thoroughly after handling. Do not eat, drink or smoke when using this product. Keep away from heat/sparks/open flames/hot surfaces. — No smoking. Ground/bond container and receiving equipment. Use explosion proof equipment. Use only non-sparking tools. Take precautionary measures against static discharges. Wear protective gloves/protective clothing and eye/face protection.

Conditions for safe storage, including any incompatibilities

Storage Conditions

Keep container tightly closed and store in a cool, dry and well-ventilated place. Store locked up. Do not store above 49°C/120°F.

Packaging Materials

Empty containers retain product residue and can be hazardous.

Incompatible Materials

Strong oxidizing agents.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Ethyl Alcohol 64-17-5	STEL: 1000 ppm	TWA: 1000 ppm TWA: 1900 mg/m ³ (vacated) TWA: 1000 ppm (vacated) TWA: 1900 mg/m ³	IDLH: 3300 ppm TWA: 1000 ppm TWA: 1900 mg/m ³
Stoddard solvent 8052-41-3	TWA: 100 ppm	TWA: 500 ppm TWA: 2900 mg/m ³ (vacated) TWA: 100 ppm (vacated) TWA: 525 mg/m ³	IDLH: 20000 mg/m ³ Ceiling: 1800 mg/m ³ 15 min TWA: 350 mg/m ³
Methanol 67-56-1	STEL: 250 ppm TWA: 200 ppm S*	TWA: 200 ppm TWA: 260 mg/m ³ (vacated) TWA: 200 ppm (vacated) TWA: 260 mg/m ³ (vacated) STEL: 250 ppm (vacated) STEL: 325 mg/m ³ (vacated) S*	IDLH: 6000 ppm TWA: 200 ppm TWA: 260 mg/m ³ STEL: 250 ppm STEL: 325 mg/m ³
Isopropyl Alcohol 67-63-0	STEL: 400 ppm TWA: 200 ppm	TWA: 400 ppm TWA: 980 mg/m ³ (vacated) TWA: 400 ppm (vacated) TWA: 980 mg/m ³ (vacated) STEL: 500 ppm (vacated) STEL: 1225 mg/m ³	IDLH: 2000 ppm TWA: 400 ppm TWA: 980 mg/m ³ STEL: 500 ppm STEL: 1225 mg/m ³

Appropriate engineering controls

Engineering Controls

Apply technical measures to comply with the occupational exposure limits. Ensure that eyewash stations and safety showers are close to the workstation location. Provide sufficient ventilation to maintain exposure below TLV(s). Any use of this product at an elevated temperature process should be thoroughly evaluated to establish and maintain safe operating conditions.

Individual protection measures, such as personal protective equipment

Eye/Face Protection	Splash proof chemical safety goggles. Refer to 29 CFR 1910.133 for eye and face protection regulations.
Skin and Body Protection	Impervious gloves, clothes and boots. Refer to 29 CFR 1910.138 for appropriate skin and body protection.
Respiratory Protection	If TLV is exceeded, use a NIOSH/MSHA approved respirator for organic vapors; Refer to 29 CFR 1910.134 for respiratory protection requirements.
General Hygiene Considerations	Handle in accordance with good industrial hygiene and safety practice.

9. PHYSICAL AND CHEMICAL PROPERTIES**Information on basic physical and chemical properties**

Physical state	Liquid	Odor	Slightly sweet, Alcohol
Appearance	Transparent to deep color liquid	Odor Threshold	Not determined
Color	Clear		

<u>Property</u>	<u>Values</u>	<u>Remarks • Method</u>
pH	Not determined	
Melting Point/Freezing Point	Not determined	
Boiling Point/Boiling Range	No data	
Flash Point	23.33 °C / 74 °F	
Evaporation Rate	3	(butyl acetate = 1)
Flammability (Solid, Gas)	Not determined	
Flammability Limits in Air		
Upper Flammability Limits	Not determined	
Lower Flammability Limit	Not determined	
Vapor Pressure	No data	
Vapor Density	No data	
Relative Density	Not determined	
Water Solubility	Not determined	
Solubility in other solvents	Not determined	
Partition Coefficient	Not determined	
Auto-ignition Temperature	Not determined	
Decomposition Temperature	Not determined	
Kinematic Viscosity	Not determined	
Dynamic Viscosity	Not determined	
Explosive Properties	Not determined	
Oxidizing Properties	Not determined	

Other Information

VOC Content	741 g/L
Density	7.5 lbs/gal @ 77°F

10. STABILITY AND REACTIVITY**Reactivity**

Not reactive under normal conditions.

Chemical Stability

Stable under recommended storage conditions.

Possibility of Hazardous Reactions

None under normal processing.

Hazardous Polymerization Hazardous polymerization does not occur.**Conditions to Avoid**

Keep away from heat, sparks and open flame.

Incompatible Materials

Strong oxidizing agents.

Hazardous Decomposition ProductsCarbon monoxide, Carbon dioxide (CO₂), Various hydrocarbons,**11. TOXICOLOGICAL INFORMATION****Information on likely routes of exposure****Product Information**

Eye Contact Avoid contact with eyes.

Skin Contact Avoid contact with skin and clothing.

Inhalation Avoid breathing vapors or mists. May cause irritation of respiratory tract.

Ingestion May be harmful if swallowed.

Component Information

Chemical Name	ATEmix (oral)	ATEmix (dermal)	Inhalation LC50
Ethyl Alcohol 64-17-5	= 7060 mg/kg (Rat)	-	= 124.7 mg/L (Rat) 4 h
Methanol 67-56-1	= 6200 mg/kg (Rat)	= 15800 mg/kg (Rabbit)	= 22500 ppm (Rat) 8 h = 64000 ppm (Rat) 4 h
Oleic Acid 112-80-1	= 25 g/kg (Rat)	-	-
Isopropyl Alcohol 67-63-0	= 1870 mg/kg (Rat)	= 4059 mg/kg (Rabbit)	= 72600 mg/m ³ (Rat) 4 h

Information on physical, chemical and toxicological effects**Symptoms** Please see section 4 of this SDS for symptoms.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Carcinogenicity

Ethanol has been shown to be carcinogenic in long-term studies only when consumed as an alcoholic beverage. Isopropyl Alcohol (IPA) is an IARC Monograph Group 3 chemical. IPA is a Group 1 when manufactured by the strong-acid process.

Chemical Name	ACGIH	IARC	NTP	OSHA
Ethyl Alcohol 64-17-5	A3	Group 1	Known	X
Isopropyl Alcohol 67-63-0		Group 3		X

Legend

ACGIH (American Conference of Governmental Industrial Hygienists)
 A3 - Animal Carcinogen
IARC (International Agency for Research on Cancer)
 Group 1 - Carcinogenic to Humans
 Group 3 IARC components are "not classifiable as human carcinogens"
NTP (National Toxicology Program)
 Known - Known Carcinogen
OSHA (Occupational Safety and Health Administration of the US Department of Labor)
 X - Present

STOT - single exposure

Causes damage to organs.

STOT - repeated exposure

Causes damage to organs through prolonged or repeated exposure.

Aspiration hazard

May be fatal if swallowed and enters airways.

Numerical measures of toxicity

The following values are calculated based on chapter 3.1 of the GHS document .

ATEmix (oral)	2,400.00 mg/kg
ATEmix (dermal)	9,760.00 mg/kg
ATEmix (inhalation-dust/mist)	15.10 mg/L
ATEmix (inhalation-vapor)	62.00 mg/L

12. ECOLOGICAL INFORMATION

Ecotoxicity

Toxic to aquatic life with long lasting effects.

Component Information

Chemical Name	Algae/aquatic plants	Fish	Crustacea
Ethyl Alcohol 64-17-5		12.0 - 16.0: 96 h Onchorhynchus mykiss mL/L LC50 static 100: 96 h Pimephales promelas mg/L LC50 static 13400 - 15100: 96 h Pimephales promelas mg/L LC50 flow-through	10800: 24 h Daphnia magna mg/L EC50 2: 48 h Daphnia magna mg/L EC50 Static 9268 - 14221: 48 h Daphnia magna mg/L LC50
Methanol 67-56-1		28200: 96 h Pimephales promelas mg/L LC50 flow-through 18 - 20: 96 h Onchorhynchus mykiss mL/L LC50 static 19500 - 20700: 96 h Onchorhynchus mykiss mg/L LC50 flow-through 100: 96 h Pimephales promelas mg/L LC50 static 13500 - 17600: 96 h Lepomis macrochirus mg/L LC50 flow-through	
Oleic Acid 112-80-1		205: 96 h Pimephales promelas mg/L LC50 static	

Isopropyl Alcohol 67-63-0	1000: 96 h Desmodemus subspicatus mg/L EC50 1000: 72 h Desmodemus subspicatus mg/L EC50	1400000: 96 h Lepomis macrochirus µg/L LC50 9640: 96 h Pimephales promelas mg/L LC50 flow-through 11130: 96 h Pimephales promelas mg/L LC50 static	13299: 48 h Daphnia magna mg/L EC50
------------------------------	---	--	-------------------------------------

Persistence/Degradability

Not determined.

Bioaccumulation

Not determined.

Mobility

Chemical Name	Partition Coefficient
Ethyl Alcohol 64-17-5	-0.32
Methanol 67-56-1	-0.77
Isopropyl Alcohol 67-63-0	0.05

Other Adverse Effects

Not determined

13. DISPOSAL CONSIDERATIONS

Waste Treatment Methods

Disposal of Wastes Disposal should be in accordance with applicable regional, national and local laws and regulations.

Contaminated Packaging Disposal should be in accordance with applicable regional, national and local laws and regulations.

US EPA Waste Number

Chemical Name	RCRA	RCRA - Basis for Listing	RCRA - D Series Wastes	RCRA - U Series Wastes
Methanol 67-56-1		Included in waste stream: F039		U154

California Hazardous Waste Status

This product contains one or more substances that are listed with the State of California as a hazardous waste

Chemical Name	California Hazardous Waste Status
Ethyl Alcohol 64-17-5	Toxic Ignitable
Methanol 67-56-1	Toxic Ignitable
Isopropyl Alcohol 67-63-0	Toxic Ignitable

14. TRANSPORT INFORMATION

Note Please see current shipping paper for most up to date shipping information, including exemptions and special circumstances.

DOT

UN/ID No UN1263
Proper Shipping Name Paint related material
Hazard Class 3
Packing Group III

IATA

UN/ID No UN1263
Proper Shipping Name Paint related material
Hazard Class 3
Packing Group III

IMDG

UN/ID No UN1263
Proper Shipping Name Paint related material
Hazard Class 3
Packing Group III
Marine Pollutant This material may meet the definition of a marine pollutant

15. REGULATORY INFORMATION

International Inventories

Chemical Name	TSCA	DSL/NDSL	EINECS/E LINCS	ENCS	IECSC	KECL	PICCS	AICS
Ethyl Alcohol	X	X	X	Present	X	Present	X	X
Stoddard solvent	X	X	X		X	Present	X	X
Water	X	X	X	X	X	Present	X	X
Methanol	X	X	X	Present	X	Present	X	X
Carnuba Wax	X	X	X		X	Present	X	X
Oleic Acid	X	X	X	Present	X	Present	X	X
Isopropyl Alcohol	X	X	X	Present	X	Present	X	X

Legend:

- TSCA** - United States Toxic Substances Control Act Section 8(b) Inventory
- DSL/NDSL** - Canadian Domestic Substances List/Non-Domestic Substances List
- EINECS/ELINCS** - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances
- ENCS** - Japan Existing and New Chemical Substances
- IECSC** - China Inventory of Existing Chemical Substances
- KECL** - Korean Existing and Evaluated Chemical Substances
- PICCS** - Philippines Inventory of Chemicals and Chemical Substances
- AICS** - Australian Inventory of Chemical Substances

US Federal Regulations

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical Name	Hazardous Substances RQs	CERCLA/SARA RQ	Reportable Quantity (RQ)
Methanol 67-56-1	5000 lb		RQ 5000 lb final RQ RQ 2270 kg final RQ

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical Name	CAS No	Weight-%	SARA 313 - Threshold Values %
Methanol - 67-56-1	67-56-1	<4	1.0
Isopropyl Alcohol - 67-63-0	67-63-0	<1	1.0

CWA (Clean Water Act)

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

US State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals.

Chemical Name	California Proposition 65
Ethyl Alcohol - 64-17-5	Carcinogen Developmental
Methanol - 67-56-1	Developmental

U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania
Ethyl Alcohol 64-17-5	X	X	X
Stoddard solvent 8052-41-3	X	X	X
Methanol 67-56-1	X	X	X
Oleic Acid 112-80-1			X
Isopropyl Alcohol 67-63-0	X	X	X

16. OTHER INFORMATION

<u>NFPA</u>	Health Hazards	Flammability	Instability	Special Hazards
	2	2	0	Not determined
<u>HMIS</u>	Health Hazards	Flammability	Physical hazards	Personal Protection
	2	2	0	Not determined

Issue Date: 23-Nov-2015
 Revision Date: 04-Dec-2015
 Revision Note: New format

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet