

# US – OSHA SAFETY DATA SHEET

Issue Date: 4/2/2015

Revision Date: 9/06/2018

## SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

**PRODUCT NAME:** Lead Shot

**OTHER PRODUCT NAMES:** Reload Lead, Magnum Shot, Chill Shot, Lawrence Brand Shot, West Coast Shot, Free Flow Shot, Ballast Shot, Radiation Shot, Buck Shot, Copper Plated Shot

**MANUFACTURER:** Mayco Manufacturing, LLC  
18 West Oxmoor Road  
Birmingham, AL 35209  
205-942-4242 (Call for additional information)

**EMERGENCY TELEPHONE NUMBER:** ChemTel – 800-255-9324

## SECTION 2: HAZARDS IDENTIFICATION

**GHS Classification:**

| Category   | Hazard and Precautionary Statements |   |
|--|-------------------------------------|---|
| <b>Health</b><br>Acute Toxicity – Category 4<br>Reproductive – Category 1A<br>Carcinogenicity – Category 1B<br>Specific Target Organ Toxicity – Category 2 | H302                                | Harmful if swallowed  |
|  | H332                                | Harmful if inhaled  |
|  | H360df                              | May damage fertility or unborn child  |
|  | H373                                | May cause damage to the central nervous system and systems for reproduction organs through prolonged or repeated exposure |
|  | P201                                | Obtain special instructions before use  |
|  | P202                                | Do not handle until all safety precautions have been read and understood  |
|  | P260                                | Do not breathe dust/vapors  |
| <b>Environmental</b><br>Aquatic Chronic – 1<br>Aquatic Acute – 1   | P281                                | Use personal protective equipment as required   |
|  | P308 + P313                         | If exposed or concerned, get medical advice/attention   |
| <b>Handling</b>  | H400                                | Very toxic to aquatic life  |
|  | H410                                | Very toxic to aquatic life with long lasting effects  |
|  | P405                                | Store locked up   |
|  | P501                                | Dispose of contents/container in accordance with local/regional/national/international regulations                        |

**GHS Label: Lead Products**



**Signal Word: DANGER!**

### SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

| Material | % by Wt.   | CAS #     | OSHA EXPOSURE LIMIT |
|----------|------------|-----------|---------------------|
| Lead     | 91 – 99.99 | 7439-92-1 | 0.05 mg/cubic meter |
| Antimony | 0.5 – 6.5  | 7440-36-0 | 0.50 mg/cubic meter |
| Arsenic  | 0.1 – 2.0  | 7440-38-2 | 0.01 mg/cubic meter |
| Copper   | 0.1 – 1.0  | 7440-50-8 | 0.10 mg/cubic meter |

### SECTION 4: FIRST AID MEASURES

**Eye Contact:** Remove contact lenses if applicable and flush eyes with water for at least 15 minutes.

**Skin Contact:** Wash skin thoroughly. If contact with molten metal, cool skin rapidly and seek medical assistance.

**Ingestion:** Do not induce vomiting. Call poison control center or doctor.

**Inhalation:** Remove from exposure and rest in a position comfortable for breathing.

**Important Symptoms & Effects, Acute & Delayed:** Lead poisoning can occur through acute or chronic doses. Symptoms include headaches, abdominal pain, memory loss, kidney failure, anemia, and change in skin tone, reproductive problems, weakness, pain, or tingling.

**Indication of Medical Attention:** If any acute or chronic symptoms arise or if feeling unwell after exposure, seek medical advice.

### SECTION 5: FIRE-FIGHTING MEASURES

**Flash Point:** Not Applicable

**Flammable Limits:** Not Applicable

**Extinguishing Media:** Dry chemical, foam or CO<sub>2</sub>. Do not use water when molten metal is present.

**Hazards Combustion Products:** Molten metals produce fume, vapor and or dust that may be toxic and/or respiratory irritants. Lead metal is not flammable or explosive. This product or its dust can react violently with strong oxidizing agents.

**Fire Fighting Procedures:** Use full-body protective clothing. Wear self-contained, full-face, positive pressure breathing apparatus.

### SECTION 6: ACCIDENTAL RELEASE MEASURES

Allow metal to cool and solidify if molten. Lead dust or particulate should be vacuumed using a vacuum with a HEPA filter or wet-swept. Place spilled materials in dry, closed containers for proper disposal or recycling. Do not dry sweep or use compressed air.

### SECTION 7: HANDLING AND STORAGE

**Handling:** Minimize dust generation and accumulation. Follow good hygiene practices. Do not eat, drink, smoke or apply personal products when handling. Avoid contact with eyes, skin, and clothing. Wear personal protective equipment as necessary and recommended in Section 8. Wash exposed skin with soap and water after handling.

**Storage:** Store away from strong oxidizers. Keep away from food and beverages. Protect from physical damage and surface oxidation.

## SECTION 8: EXPOSURE CONTROLS AND PERSONAL PROTECTION

### Exposure Limits:

| Chemical Name         | ACGIH TLV                          | OSHA PEL                       | NIOSH IDLH  |
|-----------------------|------------------------------------|--------------------------------|---|
| Lead<br>7439-92-1     | TWA: 0.15 mg/m <sup>3</sup> Pb     | TWA: 0.05 mg/m <sup>3</sup> Pb | IDLH: 100mg/m <sup>3</sup> Pb<br>TWA: 0.050 mg/m <sup>3</sup> Pb                  |
| Antimony<br>7440-36-0 | TWA: 0.5 mg/m <sup>3</sup> Sb      | TWA: 0.5 mg/m <sup>3</sup> Sb  | IDLH: 0.50 mg/m <sup>3</sup> Sb<br>TWA: 0.5 mg/m <sup>3</sup> Sb                  |
| Arsenic<br>7440-38-2  | TWA: 0.01 mg/m <sup>3</sup> ,A1 As | TWA: 0.01 mg/m <sup>3</sup> As | IDLH: 5 mg/m <sup>3</sup> As<br>TWA: 0.002 mg/m <sup>3</sup> As 15-minute ceiling |
| Copper<br>7440-50-8   | TWA: 1.0 mg/m <sup>3</sup> Cu      | TWA: 1.0 mg/m <sup>3</sup> Cu  | IDLH: 2000 mg/m <sup>3</sup> Cu<br>TWA: 1.0 mg/m <sup>3</sup> Cu                  |

**Engineering Controls:** Handle and process in well-ventilated areas. Ensure that dust-handling systems are designed in a manner to prevent the escape of dust/fume into the work area. Emergency eyewash stations and safety showers should be available in the immediate vicinity of use. Ensure compliance with local/regional/national/international regulations.

**Personal Protective Equipment:** Protective goggles, gloves, and clothing, as needed. Respiratory protection, as necessary when exposures are unknown or above the PEL.

**Eye/Face Protection:** Use safety glasses with side shields or chemical goggles.

**Skin and Body Protection:** Protective clothing is required if exposure exceeds the PEL or TLV or where the possibility of skin or eye irritation exists. Full body cotton or disposable coveralls and disposable gloves should be worn during use and handling. Clothing and gloves should be left at work site and either properly disposed or laundered after use in accordance with applicable regulations. Personal clothing, including shoes/boots, should be protected from contamination. If working with molten or hot metals use heat-resistant gloves.

**Respiratory Protection:** If exposure limits are exceeded or irritation is experienced, NIOSH approved respiratory protection should be worn as appropriate for protection from toxic dust.

**General Hygiene Considerations:** Do not eat, drink, smoke or apply cosmetics when using this product. Thoroughly wash face, hands and other exposed skin after handling or processing. Contaminated work clothing should not be allowed outside the workplace except for disposal or laundering.

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

**Physical State:** Solid

**Appearance:** Gray with bluish or silvery tint

**Odor:** N/A

**pH:** N/A

**Melting Point:** 327.43°C (621.4°F)

**Boiling Point:** 1740°C (3164°F)

**Boiling Range:** N/A

**Flash Point:** N/A

**Evaporation Rate:** N/A

**Flammability:** N/A

**Upper/Lower Flammability Limit:** N/A

**Molecular weight:** 207.21g/mol

**Viscosity:** N/A

**Decomposition Temperature:** N/A

**Auto Ignition Temperature:** N/A

**Partition Coefficient:** N/A

**Solubility:** N/A

**Specific Gravity (Relative Density):** 9.96

**Vapor Density:** N/A

**Vapor Pressure:** 1mm Hg@ 973°C (1783°F)

## SECTION 10: STABILITY AND REACTIVITY

**Reactivity:** Stable under normal conditions.

**Chemical Stability:** Stable under normal conditions.

**Possible Hazardous Reactions:** None under normal processing.

**Hazardous Polymerization:** Hazardous polymerization does not occur.

**Conditions to Avoid:** Incompatible materials

**Incompatible Materials:** Strong oxidizing agents

**Hazardous Decomposition Products:** Lead oxides

## SECTION 11: TOXICOLOGICAL INFORMATION

**Routes of Exposure:** Hazardous exposure can occur when the product is heated, oxidized or otherwise processed or damaged to create dust, vapor or fume. Main routes of exposure include ingestion and inhalation.

**Chronic and Acute Related Symptoms/Effects:** Acute ingestion of lead may cause abdominal pain, nausea, vomiting, diarrhea and severe cramping. This may lead rapidly to systemic toxicity including kidney failure, anemia, and reproductive problems, and must be treated by a physician. Chronic exposure may cause cancer or lead poisoning. Acute inhalation of lead dust may cause irritation of upper respiratory tract and lungs and can result in both acute and chronic overexposure.

**Measures of Toxicity:**

Acute Toxicity Estimate-Lead: 500 mg/kg body weight

Acute Toxicity-Antimony: LD<sub>50</sub> (mouse) – 145 mg/kg

**Carcinogenic Effects:**

May cause cancer. Lead is listed as a 2B carcinogen, likely in animals at extreme doses. Proof of carcinogenicity in humans is currently lacking.

IARC Group: 2A

National Toxicology Program (NTP) Status: Reasonably anticipated to be a human carcinogen.

**Additional Health Data:** Heavy metals, such as lead and antimony, are taken into the body primarily by inhalation and ingestions. Most inhalation problems can be avoided with adequate precautions such as ventilation and respiratory protection. Follow good personal hygiene practices to avoid inhalation and incidental ingestions. Restrict the use and presence of food, tobacco, and cosmetics to non-contaminated areas. Wash before eating, smoking or leaving the work site. Keep contaminated clothing and PPE out of non-contaminated areas. Do not allow contaminated clothing of PPE to be taken home. These products are intended for professional and industrial uses and should be isolated from children and their environment.

## SECTION 12: ECOLOGICAL INFORMATION

**Environmental Fate:** Toxic to aquatic life and terrestrial environments.

**Persistence and Degradability:** Lead is persistent in soil and sediments. No data on environmental degradation.

**Bioaccumulation Potential:** Lead bioaccumulates in animals and plants.

**Mobility in Soil:** Lead accumulates in soil but is not particularly mobile.

## SECTION 13: DISPOSAL CONSIDERATIONS

Waste materials or by-products formed during handling or processing, and contaminated packaging should be properly characterized and disposed in accordance with applicable local/regional/national/international rules and regulations or recycled as appropriate. Consult local, state or federal environmental agencies for applicable requirements.

## SECTION 14: TRANSPORT INFORMATION

The lead products covered by this Safety Data Sheet are not subject to DOT regulation. Waste materials or by-products formed during handling or processing or due to damage may be subject to regulation. Consult DOT for applicable requirements.

## SECTION 15: REGULATORY INFORMATION

**US Federal Regulations:**

**SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

| Chemical Name | CAS No.   | Weight - % | SARA 313 - Threshold Values % |
|---------------|-----------|------------|-------------------------------|
| Lead          | 7439-92-1 | 91-99.99   | 0.1                           |
| Antimony      | 7440-36-0 | 0.5 - 6.5  | 1.0                           |
| Arsenic       | 7440-38-2 | 0.1 - 2.0  | 0.1                           |
| Copper        | 7440-50-8 | 0.1 - 1.0  | 1.0                           |

**SARA 311/312 Hazard Categories**

Acute Health Hazard Yes  
 Chronic Health Hazard Yes

**CERCLA (Comprehensive Environmental Response, Compensation and Liability Act)**

Lead has an RQ (reportable quantity) of 10 pounds

**CWA (Clean Water Act)**

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

| Chemical Name        | CWA - Reportable Quantities | CWA - Toxic Pollutants | CWA - Priority Pollutants | CWA - Hazardous Substances |
|----------------------|-----------------------------|------------------------|---------------------------|----------------------------|
| Lead - 7439-92-1     | 10 lb.                      | X                      | X                         | X                          |
| Antimony - 7440-36-0 | 5000 lb.                    | X                      | X                         | X                          |
| Arsenic - 7440-38-2  | 1 lb.                       | X                      | X                         | X                          |
| Copper - 7440-50-8   | 1 lb.                       | -                      | X                         | X                          |

**TSCA (Toxic Substance Control Act)**

Lead is listed on the TSCA inventory

**U.S. State Regulations:**

**California Proposition 65  "WARNING"**

This product can expose you to chemicals including Lead and Antimony, which is known in the State of California to cause cancer and birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

| Chemical Name        | California Proposition 65 |
|----------------------|---------------------------|
| Lead - 7439-92-1     | Cancer                    |
| Antimony - 7440-36-0 | Cancer                    |
| Arsenic - 7440-38-2  | Developmental             |
| Copper - 7440-50-8   | Cancer                    |

**US State Right-to-Know Regulations**

| Chemical Name        | New Jersey | Massachusetts | Pennsylvania |
|----------------------|------------|---------------|--------------|
| Lead - 7439-92-1     | X          | X             | X            |
| Antimony - 7440-36-0 | X          | X             | X            |
| Arsenic - 7440-38-2  | X          | X             | X            |
| Copper - 7440-50-8   | X          | X             | X            |

**SECTION 16: OTHER INFORMATION**

**Issue Date:** 27-August-2018

**Last Revision Date:** 30-November-2017

**Revision Note:** More concise information. Corrected transport information. Minor reformatting.

**Disclaimer:** The information provided in this Safety Data Sheet is based upon information and sources available at the time of its preparation or revision which the manufacturer believes is reliable but is beyond its supervision or control. There is no warranty, expressed or implied, with respect to this information and the manufacturer assumes no liability resulting from its use. The manufacturer assumes no responsibility and expressly disclaims liability for loss, damage or expense arising out of or in any way connected with the handling, processing, storage, use or disposal of these products. It is the user's responsibility to determine the suitability of this product and to comply with the requirements of all applicable rules and regulations regarding the handling, use, processing, and disposal of these products.